

## UPVC FLAP VALVE DATA SHEET



### GENERAL SPECIFICATION :

- Operation pressure 6bar.
- Recommended Temperature 20C°.
- Available size is 200mm.

| Code   | D   | I   | d1 | d2  |
|--------|-----|-----|----|-----|
| FV2401 | 63  | 109 | 20 | 32  |
| FV2402 | 75  | 129 | 20 | 40  |
| FV2403 | 90  | 144 | 20 | 52  |
| FV2404 | 110 | 164 | 22 | 70  |
| FV2405 | 125 | 170 | 25 | 83  |
| FV2406 | 140 | 195 | 23 | 92  |
| FV2407 | 160 | 220 | 25 | 112 |
| FV2408 | 200 | 247 | 28 | 139 |

### PARTS:

| PART        | MATERIAL |
|-------------|----------|
| Body        | UPVC     |
| Flap        | UPVC     |
| Cap         | PP       |
| Body O-Ring | EPDM     |
| Flap O-RING | EPDM     |

- The above product meets the requirements of the European & Egyptian specifications (DIN 8063 - ISO 1452-3 – ES 848-2001).

#### Head Office.

15 Nablus St, from Shehab St,  
Floor 4, App 10, Mohandessin, A.R.E  
T. +202 33024067 F. +202 33423085

#### Factory.

2<sup>nd</sup> Industrial Zone Plot BG/9,  
Sadat City, Al Monofia Governorate A.R.E  
T. +2048 2656307 M. +201000443663

info@migagreen.com  
migagreenplast

